

全电式吹瓶机工程规格表
Fully Electric Stretch Blow Moulding Machine

	单位	PN-CS2000E	PN-CS2000E	PN-CS2000ME	PN-CS2000MVE	PN-CSS3000E	PN-CSS3000ME	PN-CS3000E	PN-CS3000ME	PN-CS3000VE	PN-CS4000E	PN-CS4000VE	
成型组规格 MOLDING	合模力 Clamping force	kg	32000	16000	16000	16000	16000	16000	16000	32000	32000	48000	48000
	模具行程 Clamping stroke	mm	160	110	110	110	110	110	110	110	110	120	120
	拉杆行程 Stretching stroke	mm	320	320	320	320	240	240	320	320	320	320	320
	底模行程 Bottom stroke	mm	60	50	80	80	50	80	60	60	60	50	50
	瓶子间距 Cavity pitch	mm	152.4	114.3	114.3	114.3	76.2	76.2	114.3	114.3	114.3	114.3	114.3
	模穴数 Number of cavity		2	2	2	2	3	3	3	3	3	4	4
	瓶型规格 CONTAINER	瓶子容量 Max container volume	ltr	3	1.5	1.5	1.5	0.6	0.6	1.5	1.5	1.5	1.5
颈部尺寸 Neck diameter range		mm	18-38	18-38	18-38	30-63	18-38	18-38	18-38	30-63	18-38	30-63	
瓶身直径 Max container diameter		mm	130	90	90	90	68	68	90	90	90	90	
瓶身高度 Max container height		mm	320	320	320	320	240	240	320	320	320	320	
坯头数 Carriage unit		pcs	45	38	58	58	57	87	68	68	72	72	
理论产能 THEORETICAL OUTPUT		bph	1800	2800	1700	1400	3800	2250	2200	2200	2200	5400	4000
电力规格 ELECTRICAL SYSTEM	总耗电量 Total power	KW	58	30	51	51	27	41	63	63	64	64	
	加热功率 Heating power	KW	55	27	48	48	24	38	59	59	59	59	
	灯管配置 Max. heating power	KW	78	38	69	69	30	48	84	84	84	84	
	空压规格 AIR SYSTEM	操作压力 Operating pressure	kg/cm ²	7	7	7	7	7	7	7	7	7	7
低耗电量 Air consuming		ltr/min	1500	1000	1000	1000	1500	1500	1500	1500	2000	1500	
吹瓶压力 Blowing pressure		kg/cm ²	35	35	35	35	35	35	35	35	35	35	
高压耗气量 Air consuming		ltr/min	3800	3200	3200	3200	3100	3200	3500	3500	6000	6000	
冷冻机规格 CHILLED WATER	操作压力 Operation pressure	kg/cm ²	2-4	2-4	2-4	2-4	2-4	2-4	2-4	2-4	2-4	2-4	
	温度范围 Temperature	℃	10-12	10-12	10-12	10-12	10-12	10-12	10-12	10-12	10-12	10-12	
	消耗量 Consuming	kcal/hr	7600	5400	5400	5400	5400	5400	7600	7600	10000	10000	
	流量 Flow rate	ltr/min	45	30	30	30	30	30	45	45	45	45	
冷却水规格 COOLING WATER	操作压力 Operation pressure	kg/cm ²	2-4	2-4	2-4	2-4	2-4	2-4	2-4	2-4	2-4	2-4	
	温度范围 Temperature	℃	30	30	30	30	30	30	30	30	30	30	
	消耗量 Consuming	kcal/hr	39000	39000	39000	39000	39000	39000	42000	42000	45000	45000	
	流量 Flow rate	ltr/min	100	130	100	100	130	100	100	100	150	150	
机台规格 MACHINE	机台尺寸 (W*D*H) Machine size	mm	3500*1950*2500	2400*2150*2500	3000*2150*2500	3000*2150*2500	2400*2150*2500	3000*2150*2500	3900*1950*2500	3900*1950*2500	4000*2150*2500	4000*2150*2500	
	机台重量 Machine weight	kg	3500	2700	3000	3000	3000	3000	6000	6000	6500	6500	

全电式吹瓶机工程规格表
Fully Electric Stretch Blow Moulding Machine

	单位	PN-CSS4000E	PN-CSS6000E	PN-CS6000E-II	PN-CS6000E-120	PN-CSS9000E-II	PN-CSS10E	
成型组规格 MOLDING	合模力 Clamping force	kg	32000	48000	60000	60000	60000	80000
	模具行程 Clamping stroke	mm	110	120	140	140	120	120
	拉杆行程 Stretching stroke	mm	240	240	320	320	240	240
	底模行程 Bottom stroke	mm	50	50	50	50	50	50
	瓶子间距 Cavity pitch	mm	76.2	76.2	114.3	120	76.2	76.2
	模穴数 Number of cavity		4	6	6	6	9	10
	瓶型规格 CONTAINER	瓶子容量 Max container volume	ltr	0.6	0.6	1.5	2	0.6
颈部尺寸 Neck diameter range		mm	18-38	18-38	18-38	18-38	18-38	18-30
瓶身直径 Max container diameter		mm	68	68	95	100	68	68
瓶身高度 Max container height		mm	240	240	320	320	240	240
坯头数 Carriage unit		pcs	92	108	102	96	153	282
理论产能 THEORETICAL OUTPUT		bph	6000	9600	8000	8000	12000	13000
电力规格 ELECTRICAL SYSTEM	总耗电量 Total power	KW	42	64	88	89	79	51
	加热功率 Heating power	KW	38	59	83	84	74	49
	灯管配置 Max. heating power	KW	63	78	138	141	114	70
	空压规格 AIR SYSTEM	操作压力 Operating pressure	kg/cm ²	7	7	7	7	7
低耗电量 Air consuming		ltr/min	1500	1500	1500	1500	1500	1500
吹瓶压力 Blowing pressure		kg/cm ²	35	35	35	35	35	35
高压耗气量 Air consuming		ltr/min	5000	6200	9800	9800	7400	6500
冷冻机规格 CHILLED WATER	操作压力 Operation pressure	kg/cm ²	2-4	2-4	2-4	2-4	2-4	2-4
	温度范围 Temperature	℃	10-12	10-12	10-12	10-12	10-12	10-12
	消耗量 Consuming	kcal/hr	7600	10000	11400	11400	11400	11400
	流量 Flow rate	ltr/min	45	45	60	60	60	90
冷却水规格 COOLING WATER	操作压力 Operation pressure	kg/cm ²	2-4	2-4	2-4	2-4	2-4	2-4
	温度范围 Temperature	℃	30	30	30	30	30	30
	消耗量 Consuming	kcal/hr	45000	45000	54000	54000	45000	50000
	流量 Flow rate	ltr/min	150	150	150	150	150	160
机台规格 MACHINE	机台尺寸 (W*D*H) Machine size	mm	3120*2100*2500	4000*2150*2500	5450*2150*2500	5400*2150*2500	5450*2150*2500	5690*2250*3200
	机台重量 Machine weight	kg	4500	6500	7000	7000	7000	10000

备注

- REMARK
1、以生产0.6L瓶的基本耗气量。All data standard indication for 0.6L bottle.
2、最终产能需依据瓶胚及瓶型而定。The actual output depends on the preform quality and bottle shape.
3、规格有变更，恕不另行通知。Specifications are subject to change without notice.
4、请提供稳定的环境温度。Please provide the stable temperature of air conditioner.