

化妆品瓶全自动吹瓶机规格表
COSMETICS SERIES

	单位 unit	PN-CS2000M	PN-CS2000MW	PN-CSS3000M	PN-CS3000M	PN-CSS6000M		
成型组规格 MOLDING	合模力 Clamping force	kg	16000	16000	16000	32000	48000	
	模具行程 Clamping stroke	mm	110	110	110	110	120	
	拉杆行程 Stretching stroke	mm	320	320	240	320	240	
	底模行程 Bottom stroke	mm	80	80	80	60	50	
	瓶子间距 Cavity pitch	mm	114.3	114.3	76.2	114.3	76.2	
	模穴数 Number of cavity		2	2	3	3	6	
	瓶型规格 CONTAINER	瓶子容量 Max container volume	ltr	1.5	1.5	0.6	1.5	0.6
		牙部尺寸 Neck diameter range	mm	18-38	30-63	18-38	18-38	18-38
瓶身直径 Max container diameter		mm	90	90	68	90	68	
瓶身高度 Max container height		mm	320	320	240	320	240	
胚头数 Carriage unit		pcs	58	58	87	68	108	
理论产能 THEORETICAL OUTPUT		bph	1400	1200	2100	2100	4500	
电力规格 ELECTRICAL SYSTEM		总耗电量 Total power	KW	51	51	41	63	83
		加热功率 Heating power	KW	48	48	38	59	78
	灯管配置 Max. heating power	KW	69	69	48	84	98	
	空压规格 AIR SYSTEM	操作压力 Operating pressure	kg/cm ²	7	7	7	7	7
低耗电量 Air consuming		ltr/min	1500	1500	1800	1500	2000	
吹瓶压力 Blowing pressure		kg/cm ²	35	35	35	35	35	
高压耗气量 Air consuming		ltr/min	2600	2600	2400	3000	4900	
冷冻机规格 CHILLED WATER	操作压力 Operation pressure	kg/cm ²	2-4	2-4	2-4	2-4	2-4	
	温度范围 Temperature	°C	10-12	10-12	10-12	10-12	10-12	
	消耗量 Consuming	kcal/hr	5400	5400	5400	7600	7600	
	流量 Flow rate	ltr/min	30	30	30	45	45	
冷却水规格 COOLING WATER	操作压力 Operation pressure	kg/cm ²	2-4	2-4	2-4	2-4	2-4	
	温度范围 Temperature	°C	30	30	30	30	30	
	消耗量 Consuming	kcal/hr	30000	30000	30000	30000	45000	
	流量 Flow rate	ltr/min	100	100	100	100	150	
机台规格 MACHINE	机台尺寸 (W*D*H) Machine size	mm	3000*2150*2500	3000*2150*2500	3000*2150*2500	3900*1950*2500	4000*2150*2500	
	机台重量 Machine weight	kg	3000	3000	3000	6000	6500	

备注

REMARK

- 1、以生产0.6L瓶的基本耗气量。All data standard indication for 0.6L bottle.
- 2、最终产能需依据瓶胚及瓶型而定。The actual output depends on the preform quality and bottle shape.
- 3、规格有变更，恕不另行通知。Specifications are subject to change without notice.
- 4、请提供稳定的环境温度。Please provide the stable temperature of air conditioner.