

油瓶/广口瓶吹瓶机工程规格表
OIL/WIDE-NECK JAR SERIES

	单元 UNIT	PJ-2000L-II	PJ-2000W	PJ-2000LE-II	PJ-2000WE	PJ-4000LE-II	PJ-2000LLE	PJ-3000LE	PJ-6000LE
成型组规格 MOLDING	合模力 Clamping force	kg	30000	30000	30000	30000	70000	70000	105000
	模具行程 Clamping stroke	mm	220	220	220	220	210	245	210
	拉杆行程 Stretching stroke	mm	320	320	320	320	350	420	350
	底模行程 Bottom stroke	mm	60	60	60	60	50	50	50
	瓶子间距 Cavity pitch	mm	225	225	225	225	190.5	266.7	228.6
	模穴数 Number of cavity	Cavities	2	2	2	2	4	2	3
	瓶子容量 Max container volume	ltr	5	5	5	5	6	10	6
瓶型规格 CONTAINER	牙部尺寸 Neck diameter range	mm	30-50	50-120	30-50	50-120	30-50	30-50	30-50
	瓶身直径 Max container diameter	mm	165	165	165	165	175	210	175
	瓶身高度 Max container height	mm	320	320	320	320	350	420	350
	胚头数 Carriage unit	pcs	66	42	66	42	118	118	114
	理论产能 THEORETICAL OUTPUT	bph	1200	1200	1300	1300	4000	1200	2200
	电力规格 ELECTRICAL SYSTEM	总耗电里 Total power	KW	59	50	59	50	83	75
加热功率 Heating power		KW	56	46	56	46	77.5	70	64.5
灯管配置 Max. heating power		KW	80	66	80	66	129	155	107.5
空压规格 AIR SYSTEM	操作压力 Operating pressure	kg/cm ²	7	7	7	7	7	7	7
	低耗电里 Air consuming	ltr/min	1500	1500	1500	1500	1000	1000	1000
	吹瓶压力 Blowing pressure	kg/cm ²	35	35	35	35	35	35	35
	高压耗气里 Air consuming	ltr/min	3100[4500]	3100[4500]	3100[4500]	3100[4500]	9000	6000	10000
冷冻机规格 CHILLED WATER	操作压力 Operation pressure	kg/cm ²	2-4	2-4	2-4	2-4	2-4	2-4	2-4
	温度范围 Temperature	°C	10-12	10-12	10-12	10-12	10-12	10-12	10-12
	消耗里 Consuming	kcal/hr	5400	5400	5400	5400	11400	11400	11400
	流量 Flow rate	ltr/min	45	45	45	45	90	90	90
冷却水规格 COOLING WATER	操作压力 Operation pressure	kg/cm ²	2-4	2-4	2-4	2-4	2-4	2-4	2-4
	温度范围 Temperature	°C	30	30	30	30	30	30	30
	消耗里 Consuming	kcal/hr	30000	30000	30000	39000	30000	30000	30000
	流量 Flow rate	ltr/min	100	100	100	130	100	100	100
机台规格 MACHINE	机台尺寸(W*D*H) Machine size	mm	3070*2090*2500	3000*2500*2500	3070*2090*2500	3000*2500*2500	4750*2050*2800	4750*2185*2150	4750*2050*2150
	机台重量 Machine weight	kg	4000	4000	4000	4000	8500	8500	15500

备注

- REMARK
- 1、以生产0.6L瓶的基本耗气里。All data standard indication for 0.6L bottle.
 - 2、最终产能需依据瓶胚及瓶型而定。The actual output depends on the preform quality and bottle shape.
 - 3、规格有变更，恕不另行通知。Specifications are subject to change without notice.
 - 4、请提供稳定的环境温度。Please provide the stable temperature of air conditioner.